



Landguard Point Limited

The Annexe

Green Farm Barn

Badwell Green, Badwell Ash

Bury St Edmunds

Suffolk IP31 3JG

Tel: +44 (0) 1359 258264

Fax: +44 (0) 1359 258910

Health and Safety Product Data Sheet

- Do not burn preserved wood.
- Wear dusk mask and goggles when cutting or sanding wood
- Wear gloves when working with wood
- Some preservatives may migrate from the treated wood into soil/water or may dislodge from the treated wood surface upon contact with skin. Wash exposed skin areas thoroughly.
- All sawdust and constructive debris should be cleaned and disposed of after construction.
- Wash work clothes separately from other household clothing before re-use.
- Preserved wood should not be used where it may come into direct contact or indirect contact with drinking water, except for uses involving incidental contact such as freshwater docks and bridges.
- Do not use preserved wood under circumstances where the preservative may become a component of food, animal feed or beehives.
- No not use preserved wood for mulch.
- Only preserved wood that is visibly clean and free of surface residue should be used.
- Use fixings, hardware or any metal products as recommended by their manufacturer.
- Do not use preserved wood in direct contact with aluminium. (Refer to the fixing recommendations overleaf which indicates which aluminium roofing nails are suitable to be used, always follow the manufacturers recommendations).
- If wood is to be used in an interior application and becomes wet during construction, it should be allowed to dry before being covered or enclosed.
- Disposal Recommendations: Preserved wood may be disposed of in landfills or burned in commercial or industrial incinerations or boilers in accordance with National and Regional regulations.
- If you desire to apply a finish to your preserved treated wood, we recommend use of oil based penetration finished that are transparent or semi-transparent. Some clear water repellents and semi-transparent stains can be applied to treated wood soon after construction. We do not recommend using paint or other film-forming finishes because long term maintenance of these finishes can be problematic. Whatever finish you use, always check the babel of the finishing product and follow the manufacturer's instructions. Apply the finishing product to a small, exposed test area of your project before finishing the entire project to ensure it provides the intended result before proceeding.
- Use fixings and other hardware which are in compliance with building regulations for the intended use.
- Mould growth can and does occur on the surface of many products, including treated or untreated wood, during prolonged surface exposure to excessive moisture conditions. To remove mould from treated wood surfaces, wood should be allowed to dry. Typically, mild soap and water can be used to remove surface mould.